

Infrarood
bediening

Binnendeel



Compact buitendeel

Infrarood
bediening

Binnendeel



Compact buitendeel

SRK ZM-S							
Type Binnenunit	SRK 20 ZM-S	SRK 25 ZM-S	SRK 35 ZM-S	SRK 50 ZM-S	SRK 63 ZM-S	SRK 71 ZM-S	SRK 80 ZM-S
Type buitenunit	SRK 20 ZM-S	SRK 25 ZM-S	SRK 35 ZM-S	SRK 50 ZM-S	SRK 63 ZM-S	SRK 71 ZM-S	SRK 80 ZM-S
Koelcapaciteit min/nom/max	1.0/2.0/2.7	1.0/2.25/2.9	1.0/3.5/3.8	1.6/5.0/5.5	2.15/6.3/7.1	2.15/7.1/8.5	2.7/8.0/8.5
Verwarmingscapaciteit	1.0/2.7/3.9	1.2/3.2/4.2	1.3/4.0/4.8	1.6/5.8/6.6	1.7/7.1/9.5	1.6/8.0/10.0	1.7/9.0/10.5
Technische gegevens set							
Koelem EER	4.55	4.03	3.47	3.23	3.58	3.29	3.02
Verwarmen COP	4.35	4.00	4.00	3.65	3.97	3.74	3.53
Koelen SEER/Energielabel	6.45/A++	6,59/A++	6,87/A++	6,1/A++	6,3/A++	6,06/A++	5,71/A+
Verwarmen ECOP/Energielabel	405/A+	4,16/A+	4,17/A+	4,07/A+	4,11/A+	4,03/A+	3,97/A+
Koudemiddel	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Geluidsdrukkniveau(Ulo/Lo/Me/Hi)	21/24/27/33	21/24/28/34	22/26/32/42	25/28/37/46	26/37/43/47	26/39/45/49	21/41/47/51
Geluidsdrukkniveau koelen/verwarmen (gem.JIS) dB(A)	47/46	48/49	50/51	51/53	49/50	53/51	56/54
Luchthoeveelheid,max.koelen/verwarmen m ³ /h	1,770/1,536	1,926/1,536	1,890/1,668	2,160/2,160	2.91	3.300	3.780
Afmeting buitenunit mm (HxBxD)	540x842x290	540x842x290	540x842x290	540x842x290	750x960x340	750x968x340	750x968x341
Afmeting Binnenunit mm (HxBxD)	294/798/229	294/798/229	294/798/229	294/798/229	318/1098/248	318/1098/248	318/1098/249
Prijs ex BTW	€ 999,00	€ 1.050,00	€ 1.250,00	€ 1.400,00	€ 1.550,00	€ 1.950,00	€ 2.200,00

